

EZ-602 HL-M

Heavy Duty High-performance Grease



EZ-602 HL-M is heavy duty high performance grease consisting of lithium complex based thickener, mineral lubricating oils & **molybdenum disulphide solid additives**.

EZ-602 HL-M is formulated to provide a heavier oil film for applications with excessive loading at slow speeds and high temperature. It's superiority in water resistance, oxidation stability, corrosion protection and high dropping point makes it a unique choice for rugged application requirements associated with mills producing primary metals, chemicals, cement, mining, textile, glass and paper.

Features & Benefits

- ▶ Excellent wear protection & good rust preventive properties
- ▶ Metal passivators for protection of alloy steel
- ▶ Higher base oil viscosity, ISO VG 460, to increase load carrying capacity
- ▶ Resistance to hot & cold water and good shear stability
- ▶ Oxidation stability extends life even at elevated temperatures
- ▶ Environment friendly product

Tips for better performance

- ▶ Ideal choice for steel, cement, mining, paper, textile & chemical industry for increased regreasing frequency

Typical Applications

- ▶ Heavy duty slow moving plain and rolling element bearings operating in the severe environment, under following conditions :
 - Heavy / shock loads
 - Water rich environment
 - High temperature
 - High level of vibrations

Operating Temperature Range

- ▶ **EZ-602 HL-M** is recommended for use over temperature range -25°C to 160°C



Technical data details should be considered representative or typical values only and should not be used for specification purposes.

Note*: Changes in the appearance of the product have no detrimental effect on the Quality /Performance of the product.

Packaging Details: Available in 20KG, 180KG.

Storage & Safety: This product is unlikely to present any significant health or safety hazard when used as recommended. Good standards of personal and industrial hygiene are to be maintained by the user - (Refer Safety Data Sheet).

Disclaimer: Information contained in this data sheet is based upon the properties and applications of use known to us. However, generally no legal liability may be deducted from such information.



ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.
Telephone: +91 - 8455 - 224700, 01, 03, 04, 06, 07, 08. Facsimile: +91 - 8455 - 224705. **Website: www.itwchemin.com**

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.
Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com

Corporate Identity Number (CIN) : U32301HR1979PTC038643

Speciality Chemicals & Lubricants Manufacturers