

RP 104S

TECHNICAL DATA SHEET

RP 104S is a premium quality corrosion preventive with dewatering properties, specifically formulated based on high flash point solvent. The solvent, after evaporation, leaves a thin oily protective film. It finds applications in most of the ferrous and non-ferrous and its alloy components for excellent protection for sea shipments. It is an ideal rust preventive compound for costly and precious components due to its superior protection in salty and humid environments.



Features & Benefits

- Excellent resistance to stain and varnish where metal-to-metal contact is present, especially with high temperature and humidity.
- This product is used as received via immersion, flow-on, flooding, electrostatically or wipe on. Dilution with any oil or solvent will decrease this preventive's performance
- Excellent protection from humid conditions.
- Good coverage due to its medium viscosity and high penetration properties.
- Good flow of material even at low temperatures
- Less consumption of oil due to moderate film
- No heavy metals in the product.
- Environmentally safe as it does not contain barium based additive.
- No hazardous ingredients as per OSHA
- Ease of Removability

Typical Applications:

- Rust preventive for export consignments especially through sea transit.
- As general purpose, industrial rust preventive oil

Mode of Application:

- Spraying
- Brushing
- Dipping

Typical properties:

Attributes	Ref. Method	Specifications
Appearance	Visual	Amber Liquid
Odor	Olfactory	Mild oil odor
Specific gravity @ 27°C	ASTM D 1298	0.82±0.02
Viscosity @ 37.8 °C	ASTM D 445	4.0±2.0 CST
Flash point	ASTM D 93	≥100 °C
Film thickness	IS 1154	3.5±0.5 Microns
Water content	KF Titration Method	0.3% Max
Salt spray protection	ASTM B117	72 Hrs. Minimum
Humidity protection	ASTM D1748	300 Hrs. Min.

- Technical data details should be considered representative or typical values only and should not be used for specification purposes.

Note*: Changes in the appearance of the product have no detrimental effect on the Quality /Performance of the product.

Packaging Details: Available in 20 & 205-liter drums.

Storage & Safety: As with all thixotropic products, a setting of the thixotropic agent can occur after longer periods of storage. The original quality can be restored by agitating. This product is unlikely to present any significant health or safety hazard when used as recommended. Good standards of personal and industrial hygiene are to be maintained by the user - (Refer Safety Data Sheet).

Disclaimer: Information contained in this data sheet is based upon the properties and applications of use known to us. However, generally no legal liability may be deducted from such information.



ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.
Telephone: +91 - 8455 - 224700, 01, 03, 04, 06, 07, 08. Facsimile: +91 - 8455 - 224705. **Website: www.itwchemin.com**

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.
Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com

Corporate Identity Number (CIN) : U32301HR1979PTC038643

Speciality Chemicals & Lubricants Manufacturers