

# Accu-Lube® LB-2000

## General Purpose MQL

### FEATURES

- General purpose near-dry machining lubricant
- Moderate to heavy-duty applications

### APPLICATIONS

- General machining, sawing and cutting
- Large diameter tapping
- Drilling & tapping small holes
- Broaching & spline rolling
- Sawing large diameter solids

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE

Keep container tightly closed in a dry and well-ventilated place.

### DISPOSAL

Dispose of in accordance with local regulations.



### PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Melting / Freezing Point	No data available
Boiling Point / Range	>400°F/>204°C
Vapor Pressure	>1
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	No data available
Color	Blue
Flash Point	>400°F/>204°C
Density	No data available
Evaporation Rate	No data available
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.92
Temperature Range	No data available
4-Ball Weld Load	No data available

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB2000	1 gal	bottle	4	34 lbs
LB2055	55 gal	drum	1	454 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved